

Accella Polyurethane Systems

Safety Data Sheet

1. Identification of Substance:

Product Name: QuadFoam 500

Supplier Identification:
Accella Polyurethane Systems

Telephone:
(770) 607-0755

Address:
100 Enterprise Drive
Cartersville, GA 30120

24-Hr. Emergency Phone Number:
CHEMTREC (800) 424-9300

Product Use: Polyurethane polyol component

2. Hazards Identification:

GHS Ratings:

Oral Toxicity	Acute Tox. 4	Oral>300+<=2000mg/kg
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: >= 2.3 < 4.0 or persistent inflammation
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5
Skin sensitizer	1	Skin sensitizer
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H302	Harmful if swallowed
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash hands thoroughly after handling
P270	Do not eat, drink or smoke when using this product
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves/protective clothing/eye protection/face protection
P281	Use personal protective equipment as required
P310	Immediately call a POISON CENTER in case of overexposure.
P321	Specific treatment is urgent (see Section 4 First Aid measures)
P330	Rinse mouth
P362	Take off contaminated clothing and wash before reuse
P363	Wash contaminated clothing before reuse
P301+P312	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P308+P313
P332+P313
P333+P313
P405
P501

If exposed or concerned: Get medical advice/attention
If skin irritation occurs: Get medical advice/attention
If skin irritation or a rash occurs: Get medical advice/attention
Store locked up
Dispose of contents/container in accordance with Section 13

Signal Word: Danger



3. Composition/Data on Components:

Chemical Name	CAS number	Weight Concentration %
2-Propanol, 1-chloro-, phosphate (3:1)	13674-84-5	20.00% - 30.00%
Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched	127087-87-0	10.00% - 20.00%
Ethanol, 2-[[2-(dimethylamino)ethyl]methylamino]-	2212-32-0	1.00% - 5.00%
Bis(2-dimethylaminoethyl) ether	3033-62-3	1.00% - 5.00%

4. First Aid Measures:

Inhalation: If inhaled and symptoms ensue, move to fresh air. If breathing is difficult, give oxygen.

After Eye Contact: Rinse opened eye for at least 15 minutes under running water.
Remove contact lenses if present and easy to do so, and continue rinsing.

After Skin Contact: Clean affected area with soap and plenty of water.

After Swallowing: Consult physician.

Notes to Physician: Treat symptomatically

5. Fire Fighting Measures:

Flash Point: N/A

LEL:

UEL:

Suitable Extinguishing Agents: Water spray, CO2, Foam, Dry chemical

Information about Protection against Explosions and Fires: Closed containers may rupture when exposed to extreme heat.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, hydrocarbons, oxides of phosphorus, hydrocarbons, traces of HCN.

Protective Equipment: Firefighters should wear a pressure demand self-contained breathing apparatus and protective clothing.

6. Accidental Release Measures:

Person-Related Safety Precautions: Avoid contact with skin and eyes.

Measures for Environmental Protection: Cover and contain spill with absorbent material. Collect for proper disposal according to local, state, and federal regulations.

7. Handling and Storage:

Information for Safe Handling: Avoid contact with skin or inhalation.

Storage Requirements: Store in dry, well ventilated area. Keep containers tightly closed. Store between 60°F-100°F. Material may settle.

8. Exposure Controls and Personal Protection:

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Propanol, 1-chloro-, phosphate (3:1) 13674-84-5	Not Established	Not Established	Not Established
Poly(oxy-1,2-ethanediyl), .alpha.-(4-nonylphenyl)-.omega.-hydroxy-, branched 127087-87-0	Not Established	Not Established	Not Established
Ethanol, 2-[[2-(dimethylamino)ethyl]methylamino]- 2212-32-0	Not Established	Not Established	Not Established
Bis(2-dimethylaminoethyl) ether 3033-62-3	Not Established	0.15 ppm STEL 0.05 ppm TWA	Not Established

Engineering Controls: No specific measures required.

General Protective and Hygienic Measures: Usual precautionary measures should be adhered to when handling chemicals.

Respiratory protection: None required if work area is properly ventilated.

Hand Protection: Protective chemical resistant gloves.

Eye Protection: Safety glasses.

Body Protection: Protective work clothing. Launder separately.

9. Physical and Chemical Properties:

Autoignition temperature: N/A Appearance: Clear to off white liquid Vapor Pressure: N/A Vapor Density: N/A Specific Gravity 1.05 Freezing point: N/A Boiling range: 80 - 342°C Evaporation rate: N/A Explosive Limits: N/A	Decomposition temperature: N/A Odor: Mild Odor threshold: N/A pH: N/A Melting point: N/A Solubility: N/A Flash point: 216°F, 102°C Flammability: N/A Partition coefficient (n-octanol/water): N/A
---	--

10. Stability and Reactivity:

Incompatible Materials: Avoid contact with isocyanates and strong oxidizing agents.

Hazardous Polymerization: Not expected to occur.

Dangerous Products of Decomposition: Oxides of carbon, oxides of nitrogen, hydrocarbons, oxides of phosphorus, hydrocarbons traces of HCN.

11. Toxicological Information:

Mixture Toxicity

- Oral Toxicity LD50: 1,313mg/kg
- Dermal Toxicity LD50: 3,088mg/kg
- Inhalation Toxicity LC50: 16mg/L

Component Toxicity

- 13674-84-5 2-Propanol, 1-chloro-, phosphate (3:1)
Oral LD50: 500 mg/kg (Rat) Dermal LD50: 1,230 mg/kg (Rabbit) Inhalation LC50: 5 mg/L (Rat)
- 2212-32-0 Ethanol, 2-[[2-(dimethylamino)ethyl]methylamino]-
Oral LD50: 2,000 mg/kg (Rat) Dermal LD50: 2,000 mg/kg (Rabbit) Inhalation LC50: 20 mg/L (Rat)
- 3033-62-3 Bis(2-dimethylaminoethyl) ether
Oral LD50: 910 mg/kg (Rat) Dermal LD50: 238 mg/kg (Rabbit) Inhalation LC50: 117 ppm (Rat)

Toxicity Values Listed if Known

Acute Toxicity:
Eyes: Irritating to eyes
Skin: Harmful in contact with skin
Inhalation: Not expected to be a route of exposure
Ingestion: Harmful if swallowed. Consult physician

Chronic Effects: Possible target organ effects.

Routes of Entry : Inhalation, ingestion, skin contact, eye contact

Target Organs: Skin, Eyes, Digestive tract, Reproductive system

Chemicals with Known or Possible Carcinogenic Effects:

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
-------------------	--------------------	-----------------	--------------------------

12. Ecological Information:

General Information: Based on experience, no adverse effects are to be expected if correct disposal procedures

have been followed as indicated in section 13. Individual component ecotoxicity listed if known.

Component Ecotoxicity

2-Propanol, 1-chloro-, phosphate (3:1) 96 Hr LC50 Brachydanio rerio: 56.2 mg/L [static]; 96 Hr LC50 Pimephales promelas: 98 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 30 mg/L [static] 48 Hr EC50 Daphnia magna: 63 mg/L 72 Hr EC50 Desmodesmus subspicatus: 45 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 4 mg/L

13. Disposal Considerations:

Recommendation: Observe local requirements. Dispose of in accordance with local/state/federal regulations.

14. Transport Information:

Not considered a dangerous good according to transport regulations unless specifically cited below:

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
---------------	-----------------------------	------------------	----------------------	---------------------

15. Regulatory Information:

OSHA HAZARD COMMUNICATION STANDARD: This material is classified as hazardous in accordance with OSHA 29 CFR 1910.1200.

SARA 311/312 Hazard Categories: Acute health hazard, chronic health hazard.

California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986)

This product contains no substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute unless otherwise listed:

New Jersey Right To Know List:

Bis(2-dimethylaminoethyl) ether 3033-62-3 1 to 5 %

All substances on listed on TSCA unless noted:

- None

16. Other Information:

Safety Data Sheet issued by Product Safety Department

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Accella Polyurethane Systems. The data on these sheets relates only to the specific material designated herein. Accella Polyurethane Systems assumes no legal responsibility for use or reliance upon this data. It is the user's responsibility to ensure that their activities comply with federal, state, or local laws.

Date revised: 3/15/17

Reviewer Revision 1

Date Prepared: 11/30/2016